




MINING & EARTHMOVER

MAGNA MA01 E3/L3

The Magna MA01 is designed for use on wheel loaders, dozers, scrapers, graders and articulated dump trucks. The tread compound provides excellent protection against cutting and abrasion.



Aggressive E3/L3 non-directional tread pattern provides superior traction in soft underfoot.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Load symbol	Tra code	Max. speed (km/h)	Load/speed index	Single max. load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Tyre weight (kg)
17.5R25	MA01	**	E3	50	167B	5450 kg/5.25 bar	14.00/1.5	1346	457	27	157
			L3	10	182A2	8500 kg/6.5 bar					
20.5R25	MA01	**	E3	50	177B	7300 kg/5.25 bar	17.00/2.0	1473	533	31	231
			L3	10	193A2	11500 kg/6.5 bar					
23.5R25	MA01	**	E3	50	185B	9250 kg/5.25 bar	19.50/2.5	1625	609	36	336
			L3	10	201A2	14500 kg/6.5 bar					



Magna Tyres Group

P.O. Box 436, 5140 AK Waalwijk, The Netherlands
Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 675 220, Fax: +31 416 820 037
Email: info@magnatyres.com, www.magnatyres.com

