



MINING & EARTHMOVER

MAGNA MA05 L5

The Magna MA05 is designed for extreme loader applications in surface mines, quarries, scrap yards and for underground mine transport.

The crown and sidewall are reinforced to prevent damage and to extend tyre life in severe operating conditions.



The extra deep L5 rock tread and reinforced shoulders and sidewalls prevent damage in severe operating conditions.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Load symbol	Tra code	Max. speed (km/h)	Load/speed index	Single max. load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Tyre weight (kg)
17.5R25	MA05	**	L5	6	182A2	8500 kg/6.5 bar	14.00/1.5	1397	470	65	251
26.5R25	MA05	**	L5	10	209A2	18500 kg/6.5 bar	22.00/3.0	1797	690	91	660
29.5R25	MA05	**	L5	10	216A2	22400 kg/6.5 bar	25.00/3.5	1905	775	100	838



Magna Tyres Group

P.O. Box 436, 5140 AK Waalwijk, The Netherlands
Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 675 220, Fax: +31 416 820 037
Email: info@magnatyres.com, www.magnatyres.com

