




# MINING & EARTHMOVER

## MAGNA MA01+ E3/L3

The Magna MA01+ is designed for use on wheel loaders, dozers, scrapers, graders and articulated dump trucks. The tread compound provides excellent protection against cutting and abrasion.



Aggressive E3/L3 non-directional tread pattern provides superior traction in soft underfoot.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Load symbol	Tra code	Max. speed (km/h)	Load/speed index	Single max. load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	Tyre weight (kg)
17.5R25	MA01+	**	E3	50	167B	5450 kg/5.25 bar	14.00/1.5	1350	445	27	tba
			L3	10	182A2	8500 kg/6.5 bar					
20.5R25	MA01+	**	E3	50	177B	7300 kg/5.25 bar	17.00/2.0	1490	520	33	235
			L3	10	193A2	11500 kg/6.5 bar					
23.5R25	MA01+	**	E3	50	185B	9250 kg/5.25 bar	19.50/2.5	1615	595	36	316
			L3	10	201A2	14500 kg/6.5 bar					
26.5R25	MA01+	**	E3	50	193B	11500 kg/5.25 bar	22.00/3.0	1750	675	37	439
			L3	10	209A2	18500 kg/6.5 bar					
29.5R25	MA01+	**	E3	50	200B	14000 kg/5.25 bar	25.00/3.5	1875	750	43	599
			L3	10	216A2	22400 kg/6.5 bar					



Magna Tyres Group

P.O. Box 436, 5140 AK Waalwijk, The Netherlands  
Elzenweg 7, 5144 MB Waalwijk, The Netherlands

Phone: +31 416 675 220, Fax: +31 416 820 037  
Email: info@magnatyres.com, www.magnatyres.com

